

□ Apparatus for retreating strip defatting **cleaning** solution using tubular **membrane**.

L20 ANSWER 73 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 2001-519055 [57] WPINDEX

DNC C2001-155318

DC D15 J01

IN KIM, T S; LEE, C H

PA (POHA-N) POHANG IND SCI RES INST

CYC 1

PI KR 2001018168 A 20010305 (200157)* 1p

ADT KR 2001018168 A KR 1999-33997 19990817

PRAI KR 1999-33997 19990817

AN 2001-519055 [57] WPINDEX

AB KR2001018168 A UPAB: 20011005

NOVELTY - An apparatus for retreating a strip defatting cleaning solution using a tubular membrane is provided to continuously recovering steel cleaning solution for recycling by combining and removing fractions having relatively large size particles and iron powder in a waste cleaning solution and filtering fine contaminated particles with the tubular membrane.

DETAILED DESCRIPTION - The apparatus consists of a dissolved air floatation pre-treatment part in which a lipophilic agglomeration plate is installed, wherein the dissolved air floatation pre-treatment part separates a waste cleaning solution in which fractions flow in are mixed with suspension by floating with pressurized **water mixed** with **air** ejected from a pressurizing tank; an electric charge agglomeration pre-treatment part separating contaminants by a difference of specific gravity by equipping with a plurality of electrode plates connected with an output of AC power generating means so that polarities are alternately reversed, thereby increasing particle sizes of the waste cleaning solution flow in from the dissolved air floatation pre-treatment part; a tubular membrane for separating the treated water which is flow in through a circulation vessel from the electric charge agglomeration pre-treatment part from filtrate and concentrate.
Dwg.0/10

BEST AVAILABLE COPY